605



NSN 5930-01-320-3605 Rotary Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-01-320	-3605
Overall Length: 7.090 inches	
Overall Height:	
3.500 inches	
Overall Width:	
2.250 inches	
Unthreaded Mounting Hole Diameter:	
0.310 inches single mounting facility	
Distance Between Mounting Facility Centers:	
2.310 inches single mounting facility	
Individual Section Quantity:	
2	
End Application:	
Used on ships service switchboard part number 1648a05g0	1 onboard 400 ft wagb coast guard vessels
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
6 each section front	
Throw Quantity:	
1 each section rear	
Mounting Method:	
Unthreaded hole single mounting facility	
Contact Voltage Rating In Volts:	
600.0 ac at sea level	
Switch Actuator Momentary Position:	
Clockwise single actuator	
Rotor Through Connection Quantity:	
1 each section	
Mounting Facility Pattern:	
Two position diagonal single mounting facility	
Switch Actuator Indexing Position Quantity:	
2 single actuator	
Terminal Type:	
Threaded stud	
Contact Switching Action:	

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

600.0 amperes resistive load ac at sea level

NSN 5930-01-320-3605

Rotary Switch - Page 2 of 2

Special Features:

Generator tld. Flashing switch

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

