NSN 5930-01-320-4084

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-320-4084

Threa	d I	Len	gth:

0.430 inches single pressure connection

Overall Length:

1.650 inches

Outside Diameter:

0.125 inches single connection

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Line

Contact Action Stimulus:

Increase

Proof Pressure:

30.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

5.00 actuation point pounds per square inch gage and 2.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas, liquefied

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Cylindrical

NSN 5930-01-320-4084

Pressure Switch - Page 2 of 2



Ī	hread	Series	Desig	nator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0