

View Online at <https://aerobasegroup.com/nsn/5930-01-320-9752>

Thread Class:

2a single threaded bushing

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Length:

5.230 inches

Body Diameter:

0.380 inches

Body Length:

2.230 inches

Temperature Sensing Element Type:

Disc or spring

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

114.00 actuation point degrees fahrenheit and 104.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Test Data Document:

81349-mil-s-28827 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unj single threaded bushing

Specification Data:

81349-mil-s-28827/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0