

View Online at <https://aerobasegroup.com/nsn/5930-01-321-4987>

Body Style:

Bushing mount

Overall Length:

Between 1.280 inches and 1.340 inches

Overall Height:

Between 1.900 inches and 2.080 inches

Overall Width:

Between 0.720 inches and 0.780 inches

Bushing Length:

0.468 inches

Body Length:

Between 1.280 inches and 1.340 inches

Body Width:

Between 0.720 inches and 0.780 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.110 inches and 0.170 inches

Actuator Height:

Between 0.530 inches and 0.590 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

3990-01-444-6174 bitum distributor

Mounting Surface To Terminal End Distance:

Between 1.030 inches and 1.090 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

Neoprene seal

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0