

View Online at <https://aerobasegroup.com/nsn/5930-01-321-8960>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

1.925 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.980 inches and 1.002 inches

**Overall Height:**

1.873 inches

**Overall Width:**

0.688 inches

**Bushing Length:**

0.516 inches

**Body Length:**

1.925 inches

**Body Width:**

0.688 inches

**Body Height:**

0.984 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.143 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.326 inches

**Actuator Height:**

0.373 inches

**Actuator Free Position Height:**

1.529 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole and threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

10.0 ounces

**Actuator Movement:**

0.030 pretravel inches and 0.219 overtravel inches and 0.001 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc and 15.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0