

View Online at <https://aerobasegroup.com/nsn/5930-01-321-8960>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

1.925 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.980 inches and 1.002 inches

Overall Height:

1.873 inches

Overall Width:

0.688 inches

Bushing Length:

0.516 inches

Body Length:

1.925 inches

Body Width:

0.688 inches

Body Height:

0.984 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.143 inches

Actuator Style:

Round

Actuator Diameter:

0.326 inches

Actuator Height:

0.373 inches

Actuator Free Position Height:

1.529 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole and threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

0.030 pretravel inches and 0.219 overtravel inches and 0.001 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0