## NSN 5930-01-322-0903

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-322-0903

## Hazardous Locations/environmental Protection: Humidity resistant and salt spray resistant and vibration resistant **Overall Length:** Between 1.160 inches and 1.260 inches **Overall Height:** 0.521 inches **Body Diameter:** 0.572 inches Mounting Slot Width: 0.140 inches **Body Height:** 0.364 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Distance Between Mounting Facility Centers:** 0.937 inches **End Application:** 5840-01-085-1604 antenna-transceiver **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between -80.0 degrees fahrenheit and 550.0 degrees fahrenheit **Mounting Method:** Bracket and slot and unthreaded hole **Features Provided:** Hermetically sealed case **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load third voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 85.00 actuation point degrees fahrenheit and 65.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

30.0 dc at sea level third voltage

## NSN 5930-01-322-0903

Thermostatic Switch - Page 2 of 2



Media For Which Designed: Gas or liquid **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Disc w/flange Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A048b0