# NSN 5930-01-322-1081

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-322-1081

#### **Inside Diameter:**

0.495 inches single connection

#### **Overall Length:**

4.562 inches

## **Overall Height:**

4.343 inches

## **Overall Width:**

3.483 inches

### **Body Height:**

2.187 inches

#### **Unthreaded Mounting Hole Diameter:**

0.203 inches

#### **Distance Between Mounting Facility Centers:**

2.250 inches

#### End Application:

Air supply system onboard 400 ft wagb c.G. Vessels

#### Pressure Switch Type:

Gage

**Mounting Method:** 

Bracket and unthreaded hole

## **Features Provided:**

Electrical access port and internally grounded

# **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

160.00 pounds per square inch

#### Mounting Facility Pattern:

Two position in-line

#### Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

#### **Terminal Type:**

Screw

# **Contact Load Current Rating:**

10.0 amperes resistive load second voltage

## Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

# Contact Adjustment Range:

+3.30/+80.00 actuation point pounds per square inch and +0.50/+77.20 deactuation point pounds per square inch

# Contact Adjustment Type:

External actuation point screw and external deactuation point screw

## **Contact Voltage Rating In Volts:**

480.0 ac at sea level third voltage

# NSN 5930-01-322-1081

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0