

View Online at <https://aerobasegroup.com/nsn/5930-01-322-1680>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

0.437 inches

Bushing Length:

0.250 inches

Body Length:

0.525 inches

Actuator Diameter:

0.160 inches

Actuator Height:

0.150 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes motor dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-8805/110 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0