NSN 5930-01-323-2381

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-323-2381

Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
4.188 inches
Overall Height:
3.250 inches
Overall Width:
2.810 inches
Unthreaded Mounting Hole Diameter:
0.201 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-10
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section periphery
Throw Quantity:
2 each section periphery
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Contact Owntoning Action.

Breaks before makes each section periphery

NSN 5930-01-323-2381

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 45.0 degrees single actuator Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0