NSN 5930-01-323-2382

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-323-2382

Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
5.376 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.201 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-10
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
4 each section periphery
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Breaks before makes each section periphery

NSN 5930-01-323-2382

Rotary Switch - Page 2 of 2

No Fiig: A052b0



Switch Actuator Positioning Increment: 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 6.0 amperes resistive load highest ac voltage rating at sea level **Special Features:** Legend plate reads temp meter; off; test; 1; 2; 3 **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector Shelf Life: N/a **Unit Of Measure: Demilitarization:**