NSN 5930-01-323-3871

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-323-3871

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture resistant and shock resistant
Overall Length:
2.960 inches
Overall Height:
0.990 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Actuator Length:
0.990 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
60liver perry class ffg; spruance class dd (963); arleigh burke class ddg; submarine miscellaneous sonar and adp systems; submarine
combat system, an/bsy- (v); forrestal class cv; an/sqq-89 surface ship asw combat system; ticonderoga class cg (47)
Mounting Surface To Terminal End Distance:
2.660 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

Feat

Criticality Code Justification:

NSN 5930-01-323-3871

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 pin

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0