NSN 5930-01-323-6829

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-323-6829

Thread Class:

2a single mounting facility

Thread Length:

0.438 inches single mounting facility

Overall Height:

1.120 inches

Overall Width:

1.120 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Specification Data:

81349-mil-s-21604/1 government specification

Shelf Life:

N/a

NSN 5930-01-323-6829

Rotary Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

