NSN 5930-01-324-2359

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-324-2359

| Hazardous Locations/environmental Protection: |
|---|
| Vibration resistant |
| Overall Length: |
| 2.126 inches |
| Overall Height: |
| 1.115 inches |
| Body Diameter: |
| 1.250 inches |
| Body Height: |
| 0.599 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.157 inches |
| Distance Between Mounting Facility Centers: |
| 1.812 inches |
| End Application: |
| Radar set an/apq150 |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 10.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 300.00 actuation point degrees fahrenheit and 260.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 115.0 ac at sea level single voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Disc w/flange |

NSN 5930-01-324-2359

Thermostatic Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0