NSN 5930-01-324-2360

Thermostatic Switch - Page 1 of 2

Hazardous Locations/environmental Protection:



View Online at https://aerobasegroup.com/nsn/5930-01-324-2360

Vibration resistant
Overall Length:
3.060 inches
Unthreaded Mounting Hole Diameter:
0.230 inches
Flangewidth:
1.440 inches
Tempurature Sensing Element Type:
Expanding shell
Mounting Facility Circle Radius:
0.313 inches
Mounting Method:
Flange and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable, preset
Contact Adjustment Range:
+40.00/+230.00 actuation point degrees fahrenheit
Contact Adjustment Type:
Internal actuation point tongue
Contact Stimulus Rating:
45.00 actuation point degrees fahrenheit
Contact Voltage Rating In Volts:
32.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/flange

N/a

Shelf Life:

NSN 5930-01-324-2360

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0