

View Online at <https://aerobasegroup.com/nsn/5930-01-324-2360>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.060 inches

Unthreaded Mounting Hole Diameter:

0.230 inches

Flangewidth:

1.440 inches

Temperature Sensing Element Type:

Expanding shell

Mounting Facility Circle Radius:

0.313 inches

Mounting Method:

Flange and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+40.00/+230.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point tongue

Contact Stimulus Rating:

45.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

32.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0