## NSN 5930-01-324-2362

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-324-2362

Th	read	I C	lass:

2b single mounting facility

#### **Hazardous Locations/environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Overall Length:** 

**3.218** inches

**Overall Height:** 

2.500 inches

**Overall Width:** 

3.000 inches

**Individual Section Quantity:** 

4

#### **Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

#### **Mounting Facility Circle Radius:**

1.156 inches single mounting facility

## **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

24 single mounting facility

#### **Thread Size:**

0.190 inches single mounting facility

## **Contact Voltage Rating In Volts:**

350.0 highest dc voltage rating at sea level

## **Mounting Facility Pattern:**

Four position circular single mounting facility

## **Switch Actuator Indexing Position Quantity:**

2 single actuator

## **Terminal Type:**

Tab w/screw

#### **Contact Switching Action:**

Breaks before makes each section periphery

## **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

## **Switch Actuator Stop Device Type:**

Fixed stop single actuator

## **Contact Load Current Rating:**

10.0 amperes resistive load lowest dc voltage rating at sea level

#### Style Designator:

Tap, circuit selector

# NSN 5930-01-324-2362

Rotary Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0