# NSN 5930-01-324-2364

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-324-2364

#### **Thread Class:**

2b single mounting facility

#### **Hazardous Locations/environmental Protection:**

Corrosion resistant and dust resistant and salt spray resistant and vibration resistant

**Overall Length:** 

0.570 inches

**Overall Height:** 

2.180 inches

**Overall Width:** 

1.800 inches

#### **Distance Between Mounting Facility Centers:**

1.562 inches single mounting facility

#### **Individual Section Quantity:**

1

#### **Operating Tempurature Range:**

-65.0/+125.0 degrees celsius

#### **End Application:**

5805-01-188-3993 central office, telephone, automatic

#### **Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

### **Actuator Type:**

Push button all actuators

## Thready Qty Per Inch (tpi):

56 single mounting facility

#### **Thread Size:**

0.086 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Mounting Facility Pattern:**

Two position in-line single mounting facility

#### **Switch Actuator Indexing Position Quantity:**

16 all actuators

#### **Terminal Type:**

Printed circuit

#### **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

#### **Readout Indicator Marking:**

1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 single section

#### **Contact Arrangement Truth Table:**

Bcd, 1 pole - 16 positions single section

#### Color:

White single indicator marking

# NSN 5930-01-324-2364

Code Indicating Wheel Switch - Page 2 of 2



Style	De	sia	nato	r:
	-	v.9		

Rectangular indicating

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A052b0