

View Online at <https://aerobasegroup.com/nsn/5930-01-325-2838>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

6.250 inches

**Overall Height:**

3.680 inches

**Overall Width:**

3.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.500 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Switch Actuator Positioning Increment:**

35.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

7.5 amperes inductive load highest ac voltage rating at sea level

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0