## NSN 5930-01-325-3168

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-325-3168 **Thread Class:** 2a single mounting facility **Thread Length:** 0.312 inches single mounting facility **Overall Length:** 1.448 inches **Overall Diameter:** 0.750 inches **Individual Section Quantity: Nonturn Device Type:** Flatted bushing at 3: 00 o'clockflatted bushing at 9: 00 o'clock **Switch Contact Basic Design:** Coded **Mounting Method:** Threaded bushing w/panel seal single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Terminal Type:** Tab, solder lug **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 125.0 milliamperes resistive load dc at sea level **Contact Arrangement Truth Table:** Bcd, 1 pole - 10 positions single section **Precious Material And Location:** Contact and terminal srufaces gold and terminal surfaces silver **Precious Material:** Gold and silver **Style Designator:** Tap, circular, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-01-325-3168

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0