

View Online at <https://aerobasegroup.com/nsn/5930-01-325-3279>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.470 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

4.230 inches

**Overall Diameter:**

2.000 inches

**Individual Section Quantity:**

5

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section periphery

**Throw Quantity:**

4 each section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks 2nd section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L04349; for navy nuclear propulsion plant products only

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0