

View Online at <https://aerobasegroup.com/nsn/5930-01-325-6102>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.313 inches

Body Diameter:

0.562 inches

Bushing Length:

0.625 inches

Body Length:

1.094 inches

Case Material:

Metal

Actuator Diameter:

Between 0.289 inches and 0.329 inches

Actuator Height:

0.438 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

1520-01-020-4216 helicopter, observation

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

81349-mil-s-8805/107 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0