

View Online at <https://aerobasegroup.com/nsn/5930-01-325-7493>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.470 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

5.660 inches

Overall Diameter:

2.000 inches

Individual Section Quantity:

8

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

0.720 inches 2nd mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

40 2nd mounting facility

Thread Size:

0.469 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Three position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0