NSN 5930-01-325-7494

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-325-7494

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

3.001 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.640 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.640 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

NSN 5930-01-325-7494

Rotary Switch - Page 2 of 2



Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0