NSN 5930-01-326-2260

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-326-2260

View Offilite at https://defobasegroup.com/his//5550-61-520-2200
Body Style:
Panel mounted
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.220 inches and 0.240 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc
Precious Material And Location:
Contact surfaces gold
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
17 socket, integrated wire termination
Specification Data:
81349-mil-s-22885/77 government specification
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5930-01-326-2260

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0