# NSN 5930-01-326-2260

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-326-2260

**Body Style:** 

Panel mounted

**Body Width:** 

0.750 inches

Body Height:

0.750 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.220 inches and 0.240 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

Red single actuator

## Maximum Voltage Rating In Volts:

28.0 dc

# Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Panel

#### **Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

#### Precious Material And Location:

Contact surfaces gold

#### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

17 socket, integrated wire termination

#### **Specification Data:**

81349-mil-s-22885/77 government specification

Shelf Life:

N/a

---

Unit Of Measure:

# NSN 5930-01-326-2260

Push Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

