

View Online at <https://aerobasegroup.com/nsn/5930-01-326-5847>

Hazardous Locations/environmental Protection:

Corrosion resistant and moisture resistant and salt spray resistant and vibration resistant

Overall Length:

3.062 inches

Unthreaded Mounting Hole Diameter:

Between 0.224 inches and 0.244 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.070 inches and 1.090 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.530 inches and 0.550 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.930 inches and 0.950 inches

Flangewidth:

1.438 inches

Temperature Sensing Element Type:

Expanding shell

Mounting Method:

Flange and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

-65.00/+300.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point tongue

Contact Stimulus Rating:

45.00 actuation point degrees celsius

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0