NSN 5930-01-326-7663

Push Switch - Page 1 of 2

Body Style:
Panel mount
Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-326-7663

| 1.200 inches |
|--|
| Overall Height: |
| 3.220 inches |
| Overall Width: |
| Between 0.950 inches and 0.970 inches |
| Body Length: |
| 1.200 inches |
| Body Width: |
| Between 0.950 inches and 0.970 inches |
| Body Height: |
| 3.110 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| Between 1.020 inches and 1.050 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| Between 0.164 inches and 0.210 inches |
| Actuator Width: |
| Between 0.720 inches and 0.750 inches |
| Actuator Color: |
| Blue single actuator and blue single actuator |
| Illuminated Actuator Color: |
| Blue single actuator and blue single actuator |
| Actuator Inscription: |
| Dff/df single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| 1430-01-042-4916 platoon command post, guided missile |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

NSN 5930-01-326-7663

Push Switch - Page 2 of 2



| Special Features: |
|--|
| Horizontal split lens |
| Precious Material And Location: |
| Contacts silver |
| Terminal Type And Quantity: |
| 12 turret and 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A053a0