

View Online at <https://aerobasegroup.com/nsn/5930-01-326-8492>

Thread Class:

2b all pressure connection

Inside Diameter:

0.438 inches all connections

Hazardous Locations/environmental Protection:

Vibration resistant and watertight

Overall Length:

8.000 inches

Overall Height:

2.688 inches

Overall Width:

5.531 inches

Body Length:

2.750 inches

Body Width:

5.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

900.00 pounds per square inch gage

Thread Size:

0.438 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load eighth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+50.00/+800.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fifth voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0