# NSN 5930-01-327-2801

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-327-2801

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.120 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

## Actuator Length:

0.620 inches

## Actuator Style:

Rectangular

## Actuator Height:

Between 0.090 inches and 0.120 inches

## Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator and white single actuator

#### Illuminated Actuator Color:

Clear single actuator and clear single actuator

#### **Actuator Inscription:**

Cpu 1/2 single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

#### Mounting Surface To Terminal End Distance:

2.756 inches

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

### Features Provided:

Horizontal split lens

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit



# NSN 5930-01-327-2801

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## Precious Material And Location:

Contacts gold

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A053a0