## NSN 5930-01-327-2802

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-327-2802

3
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.120 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.090 inches and 0.120 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Natural single actuator and natural single actuator
Actuator Inscription:
Cpu 3/4 single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.756 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-327-2802

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0