# NSN 5930-01-327-4234

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-327-4234

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.188 inches
Overall Height:
11.687 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
6.000 inches
Bulb Diameter:
1.125 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
195.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, double make, momentary action
Terminal Type:
Screw
Contact Load Current Rating:

16.0 amperes inductive load first voltage8.0 amperes inductive load second voltage4.0 amperes inductive load third voltage3.2 amperes inductive load fourth voltage9.6 amperes inductive load fifth voltage4.8 amperes inductive load sixth voltage2.5 amperes inductive load seventh voltage2.0 amperes inductive load eighth voltage

## NSN 5930-01-327-4234

Thermostatic Switch - Page 2 of 2



#### **Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

### **Contact Adjustment Range:**

+90.00/+165.00 actuation point degrees fahrenheit and +90.00/+165.00 deactuation point degrees fahrenheit

### **Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

### **Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage550.0 ac at sea level fourth ea level eighth

voltage115.0 dc at sea level fifth voltage230.0 dc at sea level sixth voltage440.0 dc at sea level seventh voltage550.0 dc at sea
voltage
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Shelf Life:
N/a

**Demilitarization:** 

**Unit Of Measure:** 

No

Fiig:

A048b0