

View Online at <https://aerobasegroup.com/nsn/5930-01-327-6455>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

5.930 inches

**Overall Height:**

2.630 inches

**Overall Width:**

3.500 inches

**Body Length:**

3.600 inches

**Unthreaded Mounting Hole Diameter:**

0.270 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.720 inches

**Longest Vertical Distance Between Mounting Centers:**

2.720 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

475.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes inductive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+3.00/+150.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point knob

**Contact Stimulus Rating:**

3.20 actuation point pounds per square inch gage and 4.80 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

600.0 dc at sea level fifth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

50.0 third voltage and 60.0 third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0