

View Online at <https://aerobasegroup.com/nsn/5930-01-327-6455>

Inside Diameter:

0.250 inches single connection

Overall Length:

5.930 inches

Overall Height:

2.630 inches

Overall Width:

3.500 inches

Body Length:

3.600 inches

Unthreaded Mounting Hole Diameter:

0.270 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

475.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+3.00/+150.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point knob

Contact Stimulus Rating:

3.20 actuation point pounds per square inch gage and 4.80 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

600.0 dc at sea level fifth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

50.0 third voltage and 60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0