

View Online at <https://aerobasegroup.com/nsn/5930-01-328-4102>

Thread Class:

2b single mounting facility

Overall Length:

5.310 inches

Overall Height:

2.280 inches

Overall Width:

2.090 inches

Shaft Diameter:

0.406 inches single actuator

Shaft Length:

0.940 inches single actuator

Distance Between Mounting Facility Centers:

1.187 inches single mounting facility

Individual Section Quantity:

6

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section periphery

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

36 single mounting facility

Thread Size:

0.153 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 ac at sea level125.0 highest dc voltage rating at sea level24.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level2.5 amperes resistive load highest dc voltage rating at sea level25.0 amperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0