NSN 5930-01-328-5445

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-328-5445

Thread Class:

2a single mounting facility

Thread Length:

0.203 inches single mounting facility and 0.233 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant and shock resistant and vibration resistant

Overall Length:

Between 1.428 inches and 1.468 inches

First Flat Length:

0.569 inches single actuator and 0.579 inches single actuator

Flat Height:

0.091 inches single actuator and 0.095 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.127 inches single actuator

Shaft Length:

0.616 inches single actuator and 0.656 inches single actuator

Overall Diameter:

Between 0.657 inches and 0.719 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

End Application:

Radio set an/arc-187

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section periphery

Throw Quantity:

4 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Dummy terminal

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

NSN 5930-01-328-5445

Rotary Switch - Page 2 of 2



	_
Shaff	Type:
Ullait	iype.

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+2.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0