## NSN 5930-01-328-5449

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-328-5449

Body Style:					
Panel mounted					
Hazardous Locations/environmental Protection:					
Explosion proof and humidity resistant					
Overall Length:					
3.116 inches					
Overall Height:					
0.760 inches					
Overall Width:					
0.760 inches					
Body Width:					
0.750 inches					
Body Height:					
0.750 inches					
Case Material:					
Metal					
Actuator Length:					
Between 0.615 inches and 0.625 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
Between 0.090 inches and 0.120 inches					
Actuator Width:					
Between 0.615 inches and 0.625 inches					
Actuator Color:					
Black single actuator					
Illuminated Actuator Color:					
Clear single actuator					
Actuator Inscription:					
Ewo push single actuator					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
Mounting Surface To Terminal End Distance:					
2.996 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Full display lens					
Nonpile-up Contact Arrangement:					
4 pole, double throw, one position momentary single switch unit					

## NSN 5930-01-328-5449

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

D۳	acione	Matoria	I And	Location:
71	ecious	wateria	II Ana	Location.

Contacts silver

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0