## NSN 5930-01-328-5855

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-328-5855

Th	read	d C	lass:

3a single pressure connection

**Hazardous Locations/environmental Protection:** 

Explosion proof

Overall Length:

4.150 inches

**Outside Diameter:** 

0.438 inches single connection

**Pressure Switch Type:** 

Gage

Width Across Flats:

0.870 inches

**Operating Tempurature Rating:** 

Between -40.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:** 

Inlet connection

**Features Provided:** 

Hermetically sealed case

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

1000.00 pounds per square inch gage

**Thread Size:** 

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Wire lead

**Contact Load Current Rating:** 

5.0 amperes resistive load third voltage and 3.0 amperes inductive load third voltage

**Contact Adjustability:** 

Actuation point not adjustable

**Contact Stimulus Rating:** 

20.00 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level third voltage

**Pressure Connector Type:** 

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Cylindrical

## NSN 5930-01-328-5855

Pressure Switch - Page 2 of 2



Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0