NSN 5930-01-328-5856

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-328-5856

| Th | read | d C | lass: |
|----|------|-----|-------|
| | | | |

3a single pressure connection

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.430 inches

Outside Diameter:

0.438 inches single connection

Pressure Switch Type:

Gage

Width Across Flats:

0.870 inches

Operating Tempurature Rating:

Between -40.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load third voltage and 3.0 amperes inductive load third voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

150.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

NSN 5930-01-328-5856

Pressure Switch - Page 2 of 2



| T | h r | ead | Series | Design | nator: |
|---|------------|-----|---------------|--------|--------|
| | | | | | |

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0