

View Online at <https://aerobasegroup.com/nsn/5930-01-328-5857>

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

5.190 inches

Overall Height:

5.775 inches

Overall Width:

2.810 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.280 inches

Longest Horizontal Distance Between Mounting Centers:

2.400 inches

Shortest Horizontal Distance Between Mounting Centers:

0.660 inches

Longest Vertical Distance Between Mounting Centers:

3.280 inches

Temperature Sensing Element Type:

Immersion well

Operating Temperature Rating:

Between 20.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

81.00 actuation point degrees fahrenheit and 65.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0