

View Online at <https://aerobasegroup.com/nsn/5930-01-329-1233>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

1.030 inches

Bushing Length:

0.830 inches

Body Length:

2.440 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.770 inches and 1.810 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

Between 0.104 inches and 0.130 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 152.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 50.000 milliamperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0