NSN 5930-01-329-2760

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-329-2760 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.500 inches **Overall Height:** 1.285 inches **Overall Width:** 0.450 inches **Bushing Length:** 0.370 inches **Body Length:** 0.500 inches **Body Width:** 0.450 inches **Body Height:** 0.410 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Diameter:** 0.115 inches **Actuator Height:** 0.410 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.250 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit

NSN 5930-01-329-2760

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage	Contact	Load	Current	Rating A	At Maximum	Rated	Voltage
--	---------	------	---------	----------	------------	-------	---------

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0