

View Online at <https://aerobasegroup.com/nsn/5930-01-329-4309>

Thread Class:

3b first pressure connection

Inside Diameter:

0.750 inches first connection

Thread Length:

0.758 inches third threaded bushing

Overall Length:

2.935 inches

Outside Diameter:

0.875 inches second connection

Overall Height:

Between 2.620 inches and 2.820 inches

Body Diameter:

Between 2.350 inches and 2.390 inches

Body Height:

1.442 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 32.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Line

Thready Qty Per Inch (tpi):

24 third threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.875 inches second pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

50.0 milliamperes inductive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

8.90 actuation point gallons per minute and 9.30 deactuation point gallons per minute

Contact Voltage Rating In Volts:

50.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal first connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Uns third threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0