NSN 5930-01-329-4313

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-329-4313

Thread Class: 2a single threaded stud **Thread Length:** 0.375 inches single threaded stud **Overall Length:** Between 1.465 inches and 1.510 inches **Overall Height:** 0.360 inches **Body Diameter:** 0.720 inches **Body Height:** 0.360 inches **End Application:** An/tyq-2 (v) 1, tactical air operations central **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between -10.0 degrees fahrenheit and 300.0 degrees fahrenheit **Mounting Method:** Threaded stud **Features Provided:** Hermetically sealed case Thready Qty Per Inch (tpi): 32 single threaded stud **Contact Action Stimulus:** Increase **Thread Size:** 0.138 inches single threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage **Contact Adjustability:** Actuation point not adjustable **Contact Stimulus Rating:** 165.00 actuation point degrees fahrenheit **Contact Voltage Rating In Volts:**

Frequency In Hertz:

28.0 dc at sea level second voltage

60.0 first voltage

NSN 5930-01-329-4313

Thermostatic Switch - Page 2 of 2

Media For Which Designed:

Gas



Style Designator:
Disc w/flange
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single threaded stud
Specification Data:
81349-mil-s-24236/20 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A048b0