

View Online at <https://aerobasegroup.com/nsn/5930-01-329-4316>

**Body Style:**

Bushing mount

**Overall Length:**

0.572 inches

**Overall Height:**

2.215 inches

**Overall Width:**

0.556 inches

**Bushing Length:**

Between 0.413 inches and 0.463 inches

**Body Length:**

0.572 inches

**Body Width:**

0.556 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.420 inches and 0.432 inches

**Actuator Height:**

Between 0.936 inches and 1.030 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Weapon systems-oliver perry class ffg; tarawa class lha; austin ship class lpd-4 amphibious transport docks; spruance class dd (963); arleigh burke class ddg; wasp class lhd; ticonderoga class cg (47); nimitz class cvn; forrestal class cv; tactical air opns module (an/tyq (23)

**Mounting Surface To Terminal End Distance:**

0.706 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

96906-ms21027 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0