NSN 5930-01-329-7746

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-329-7746

| Body Style: | | | |
|---|--|--|--|
| Bushing mounted | | | |
| Overall Length: | | | |
| 1.516 inches | | | |
| Overall Height: | | | |
| 0.551 inches | | | |
| Overall Width: | | | |
| 0.551 inches | | | |
| Body Diameter: | | | |
| 0.391 inches | | | |
| Bushing Length: | | | |
| 0.559 inches | | | |
| Body Length: | | | |
| 0.452 inches | | | |
| Case Material: | | | |
| Metal | | | |
| Actuator Diameter: | | | |
| 0.457 inches | | | |
| Actuator Height: | | | |
| 0.138 inches | | | |
| Actuator Color: | | | |
| Natural single actuator | | | |
| Illuminated Actuator Color: | | | |
| Red single actuator | | | |
| Maximum Voltage Rating In Volts: | | | |
| 250.0 ac and 30.0 dc | | | |
| Inclosure Type: | | | |
| Fully enclosed | | | |
| Mounting Method: | | | |
| Threaded bushing | | | |
| Thready Qty Per Inch (tpi): | | | |
| 32 | | | |
| Thread Size: | | | |
| 0.469 inches | | | |
| Nonpile-up Contact Arrangement: | | | |
| 1 pole, double throw, one position momentary single switch unit | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | |
| 1.000 amperes resistive dc and 1.000 amperes resistive ac | | | |
| Special Features: | | | |
| Light-emitting diode provided | | | |

Contacts silver

Precious Material And Location:

NSN 5930-01-329-7746

Push Switch - Page 2 of 2



| Ihread | Series | Designator |
|--------|--------|------------|
| Uns | | |

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0