

View Online at <https://aerobasegroup.com/nsn/5930-01-330-6854>

**Thread Class:**

2a 2nd mounting facility

**Thread Length:**

0.437 inches 2nd mounting facility

**Overall Length:**

2.591 inches

**Overall Height:**

1.470 inches

**Overall Width:**

1.100 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.437 inches single actuator

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

10 each section rear

**Mounting Method:**

Printed circuit 1st mounting facilitythreaded bushing w/panel seal 2nd mounting facility

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level250.0 milliamperes inductive load dc at sea level and 1.25 amperes resistive load dc at sea level

**Precious Material And Location:**

Terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular panel mount

**Thread Series Designator:**

Unef 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0