

View Online at <https://aerobasegroup.com/nsn/5930-01-330-7494>

**Thread Class:**

2a single mounting facility

**Thread Length:**

15.50 millimeters single mounting facility

**Overall Length:**

46.5 millimeters

**First Flat Length:**

8.0 millimeters single actuator

**Flat Height:**

4.0 millimeters single actuator

**Shaft Diameter:**

6.3 millimeters single actuator

**Shaft Length:**

10.0 millimeters single actuator

**Overall Diameter:**

34.0 millimeters

**Nonturn Device Radius:**

22.0 millimeters at 7: 30 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 7: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.4375 inches single mounting facility

**Contact Voltage Rating In Volts:**

12.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

11.0 amperes resistive load dc at sea level

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0