

View Online at <https://aerobasegroup.com/nsn/5930-01-330-7494>

Thread Class:

2a single mounting facility

Thread Length:

15.50 millimeters single mounting facility

Overall Length:

46.5 millimeters

First Flat Length:

8.0 millimeters single actuator

Flat Height:

4.0 millimeters single actuator

Shaft Diameter:

6.3 millimeters single actuator

Shaft Length:

10.0 millimeters single actuator

Overall Diameter:

34.0 millimeters

Nonturn Device Radius:

22.0 millimeters at 7: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 7: 30 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.4375 inches single mounting facility

Contact Voltage Rating In Volts:

12.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

11.0 amperes resistive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0