# NSN 5930-01-330-7669

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-330-7669

# **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Driptight and fungus resistant and salt spray resistant and shock resistant and vibration resistant

#### **Overall Length:**

0.685 inches

#### **Overall Height:**

2.220 inches

#### **Overall Width:**

0.685 inches

#### **Body Length:**

0.685 inches

#### Body Width:

0.685 inches

# **Body Height:**

1.250 inches

# Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# **Criticality Code Justification:**

Feat

# Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 0.700 amperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 0.700 amperes lamp ac

#### **Special Features:**

Lamp terminals provided; positive keyed hub number 04

#### **Terminal Type And Quantity:**

12 tab, solder lug

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A053a0